

VC15V7EA

15" CCTV LCD Display Monitor

Features :

15" TFT XGA LCD

1024*768

250 cd/m²

400:1

25ms

Optional Multimedia Features

Optional Kensington Lock

Optional VESA Mount



LCD Display

| | |
|----------------|-----------------------------------|
| Display Type | : 15" active matrix TFT LCD panel |
| Pixel Pitch | : 0.297(H)×0.297(V) mm |
| Display Area | : 304.128(H)×228.096(W) mm |
| Viewing Area | : L/R +70°~-70° , U/D +55°~-45° |
| Brightness | : 250 cd/m ² |
| Contrast Ratio | : 400:1 |
| Response Time | : 25ms |

Operation Features

| | |
|----------------|---------------------------|
| Input Range | : 30KHZ-60KHZ / 50HZ-75HZ |
| Display Colors | : 262,144 |
| Resolution | : XGA 1024x768@75Hz |

Humidity and Temperature Condition

| | |
|-----------|---------------------|
| Operation | : 20%~80%, 0°~45° |
| Storage | : 20%~80%, -20°~60° |

Features Selection

| | |
|---------------|--|
| PC | : Analog - 15 pin D-sub |
| Multimedia | : S-Video In/ RCA- Video In/ BNC-Video In/ Out/ Audio In (Option) |
| Video Mode | : NTSC/PAL/SECAM Auto Scanning |
| Audio Speaker | : 2W |

User Control

| | |
|-----------------|--|
| Front Control | : Auto Adjust, Menu, Select+, Select-, Power |
| Add on Function | : Kensington Lock (Option) |

Physical Specification

| | |
|-----------|-----------------------------------|
| Dimension | : 405(H)×400(W)×170(D) mm typical |
| Weight | : 6.5 KGS |

Power

| | |
|--------------|----------------------|
| Source | : DC12V/3A |
| Power Saving | : VESA DPMS Standard |
| Consumption | : 30W (max) |

Regulation

| | |
|--------------|--|
| Safety & EMI | : UL, CSA, TUV/GS, CE, VCCI, FCC(DoC), : BSMI |
|--------------|--|